

SMS-080

Large-cable stripping machine



Power

1.5 kW

Stripping speed

20 m/min

Weight

65 kg

SMS-080 opens cable insulation with upper and lower blades. The enclosed gear-and-chain transmission drives the cable through opposed cutting positions; this configuration is for unarmored cable.

SMS-080 采用上下刀对剖外皮，配有封闭齿轮链条传动，用于非铠装线缆剥皮。

Built for your application

产品用途与结构特点

SMS-080 opens cable insulation with upper and lower blades. The enclosed gear-and-chain transmission drives the cable through opposed cutting positions; this configuration is for unarmored cable.

SMS-080 采用上下刀对剖外皮，配有封闭齿轮链条传动，用于非铠装线缆剥皮。

Product highlights

01 Upper and lower cutting blades

02 Enclosed gear-and-chain drive

03 Unarmored cable applications

Workshop wire processing

Suitable for a dedicated wire-recovery workstation. Choose the model and drive arrangement around cable size, daily working volume and available workspace.

适用于独立线材回收工位。根据线径、日常处理量和工作空间选择机型及驱动方式。

Plan your configuration

- Cable outside diameter and insulation type
- Armored or unarmored cable construction
- Available voltage, frequency and phase
- Expected daily throughput and destination

请提供物料照片、尺寸范围、处理量、电源条件与收货国家，以便确定合适配置。

Technical specifications

技术规格与配置

Technical specifications

Specification	Value
Model	SMS-080
Power	1.5 kW
Voltage	110 V/220 V
Blades	2
Feed openings	1
Stripping speed	20 m/min
Dimensions	60 × 38 × 58 cm
Weight	65 kg

Final configuration, electrical supply and included accessories are confirmed in the quotation.

A closer look

产品结构细节



Product view 02

Talk to SENDUO

Taizhou Senduo Environmental Protection Equipment
Technology Co., Ltd
台州森多环保设备科技有限公司

Building 3, Huifeng Science and Technology Industrial Park,
Fengjiang Street, Luqiao District, Taizhou City, Zhejiang
Province, China

中国浙江省台州市路桥区峰江街道汇峰科技产业园3号楼

SALES & TECHNICAL ENQUIRIES

Lilian | Mobile / WhatsApp

+86 158 6868 6022

Ken Shi | Mobile / WhatsApp

+86 156 0588 2166

sales@sd-recycle.com

sales@sen-duo.com

sen-duo.com | wirestrippermachine.com